



**Double Joint
Plain Bearings
Type UJDP in Steel**

UJDP Properties		Further bore types as below available on request
Maximum working angle	90 degrees	
Maximum speed	1000 rpm	
Maximum power	6kW	
Maximum torque	600 Nm	
Higher power and torques are available using larger diameter or needle roller bearing joints : please enquire		
NB : It is recommended that all plain bearing joints should be used with a protective gaiter to assist lubrication and help arrest the ingress of dirt.		

Stock No	Bore d H7	Diameter D	Overall length L3	Pivot to face centre L1	Pivot to pivot centre L4	Hub length C	Weight KG	Gaiter type
UJDP16X6	6	16	56	17	22	8	0.08	UJG01M16
UJDP16X8	8	16	62	20	22	11	0.08	UJG01M16
UJDP22X10	10	22	74	24	26	12	0.15	UJG03M22
UJDP25X12	12	25	86	28	30	13	0.25	UJG04M25
UJDP28X14	14	28	96	30	36	14	0.4	UJG05M28
UJDP32X16	16	32	104	34	36	16	0.45	UJG1M32
UJDP36X18	18	36	114	37	40	17	0.7	UJG2M36
UJDP42X20	20	42	128	41	46	18	1	UJG3M42
UJDP45X22	22	45	145	47.5	50	22	1.55	UJG4M45
UJDP50X25	25	50	163	54	55	26	2	UJG5M50

For further sizes please enquire
 All dimensions in mm unless specified
 If a dimension is critical to your application please contact our sales department for confirmation.
 Please note : errors and omissions excepted.