



**Double Joint  
Plain Bearings  
UNBORED LONG  
Type UJDPL in Steel**

UJDPL Properties		Further bore types as below available on request	
Maximum working angle	90 degrees		
Maximum speed	1000 rpm		
Maximum power	6kW		
Maximum torque	600 Nm		
Higher power and torques are available using larger diameter or needle roller bearing joints : please enquire			
NB : It is recommended that all plain bearing joints should be used with a protective gaiter to assist lubrication and help arrest the ingress of dirt.			

Stock No	Bore	Diameter D	Overall length L2	Pivot centre L1	Pivot to pivot centre L4	Hub length C	Weight KG	Gaiter type
UJDPL16XSOL	SOLID	16	67	22.5	22	13.5	-	UJG01M16
UJDPL22XSOL	SOLID	22	115	44.5	26	32.5	-	UJG03M22
UJDPL25XSOL	SOLID	25	123	46.5	30	31.5	-	UJG04M25
UJDPL28XSOL	SOLID	28	130	47	36	31	-	UJG05M28
UJDPL32XSOL	SOLID	32	143	53	37	35	-	UJG1M32
UJDPL36XSOL	SOLID	36	155	57.5	40	37.5	-	UJG2M36
UJDPL42XSOL	SOLID	42	162	57.5	47	34.5	-	UJG3M42
UJDPL45XSOL	SOLID	45	173	61.5	50	36	-	UJG4M45
UJDPL50XSOL	SOLID	50	220	82.5	55	54.5	-	UJG5M50
UJDPL58XSOL	SOLID	58	245	88.5	68	55	-	UJG5M58

For further sizes please enquire  
 All dimensions in mm unless specified  
 If a dimension is critical to your application please contact our sales department for confirmation.  
 Please note : errors and omissions excepted.