



Oil Impregnated Sintered Bronze Bushes

Metric: Flanged

All Dimensions in mm unless stated otherwise

Type Ref.	Ød (G7)			ØD (s7)			ØD ₁	e	Available Lengths L
	Basic	Min	Max	Basic	Min	Max			
AMF 0103	1	1.002	1.012	3	3.014	3.024	5	1	02
	1.5	1.502	1.512	4	4.019	4.031	6	1	02
AMF 0205	2	2.002	2.012	5	5.019	5.031	8	1.5	03
	2.5	2.502	2.512	6	6.019	6.031	9	1.5	03
AMF 0306	3	3.002	3.012	6	6.019	6.031	9	1.5	04
AMF 0408	4	4.004	4.016	8	8.023	8.038	12	2	03 04 06 08 12
AMF 0509	5	5.004	5.016	9	9.023	9.038	13	2	04 05 08
AMF 0610	6	6.004	6.016	10	10.023	10.038	14	2	04 06 10
AMF 0711	7	7.005	7.020	11	11.028	11.046	15	2	05 08
AMF 0812	8	8.005	8.020	12	12.028	12.046	16	2	06 08 12 16
AMF 0914	9	9.005	9.020	14	14.028	14.046	19	2.5	06 10 14
AMF 1013	10	10.005	10.020	13	13.028	13.046	17	2.5	10 16 20
AMF 1015	10	10.005	10.020	15	15.028	15.046	21	3	10 16 20
AMF 1016	10	10.005	10.020	16	16.028	16.046	22	3	08 10 16
AMF 1215	12	12.006	12.024	15	15.028	15.046	21	3	08 10 16
AMF 1217	12	12.006	12.024	17	17.028	17.046	23	3	12 16 20 25
AMF 1218	12	12.006	12.024	18	18.028	18.046	24	3	08 12 20
AMF 1420	14	14.006	14.024	20	20.035	20.056	26	3	10 14 20
AMF 1519	15	15.006	15.024	19	19.035	19.056	25	3	16 20 25
AMF 1521	15	15.006	15.024	21	21.035	21.056	27	3	10 15 20 25
AMF 1620	16	16.006	16.024	20	20.035	20.056	27	3	16 20 25
AMF 1622	16	16.006	16.024	22	22.035	22.056	28	3	12 16 20 25
AMF 1824	18	18.006	18.024	24	24.035	24.056	30	3	12 18 22 30
AMF 2024	20	20.007	20.028	24	24.035	24.056	30	3	16 20 25
AMF 2026	20	20.007	20.028	26	26.035	26.056	32	3	15 20 25 30
AMF 2228	22	22.007	22.028	28	28.035	28.056	34	3	15 20 25 30
AMF 2530	25	25.007	25.028	30	30.035	30.056	39	3.5	20 25 32
AMF 2532	25	25.007	25.028	32	32.043	32.068	39	3.5	20 25 30
AMF 2836	28	28.007	28.028	36	36.043	36.068	44	4	20 25 30
AMF 3038	30	30.007	30.028	38	38.043	38.068	46	4	20 25 30
AMF 3238	32	32.009	32.034	38	38.043	38.068	46	4	20 25 32
AMF 3240	32	32.009	32.034	40	40.043	40.068	48	4	20 25 30
AMF 3545	35	35.009	35.034	45	45.043	45.068	55	5	25 35 45
AMF 3848	38	38.009	38.034	48	48.043	48.068	58	5	25 35 45
AMF 4046	40	40.009	40.034	46	46.043	46.068	56	5	25 32 40
AMF 4050	40	40.009	40.034	50	50.043	50.068	60	5	25 30 40 50

Type Ref.	Ød (G8)			ØD (s8)			ØD ₁	e	Available Lengths L
	Basic	Min	Max	Basic	Min	Max			
AMF 4252	42	42.009	42.048	52	52.053	52.099	62	5	30 40 50
AMF 4555	45	45.009	45.048	55	55.053	55.099	65	5	35 45 55
AMF 5060	50	50.009	50.048	60	60.053	60.099	70	5	32 40 50

Please note : errors and omissions excepted.