



**Single Joint  
Plain Bearings  
Type UJSP in Steel**

UJSP Properties		Further bore types as below available on request	
Maximum working angle	45 degrees		
Maximum speed	1000 rpm		
Maximum power	6kW		
Maximum torque	600 Nm		
Higher power and torques are available using larger diameter or needle roller bearing joints : please enquire			
NB : It is recommended that all plain bearing joints should be used with a protective gaiter to assist lubrication and help arrest the ingress of dirt.			

Stock No	Bore d H7	Diameter D	Overall length L2	Pivot centre L1	Hub length C	Weight KG	Gaiter type
UJSP16X6	6	16	34	17	8	0.05	UJG01M16
UJSP16X8	8	16	40	20	11	0.05	UJG01M16
UJSP22X10	10	22	48	24	12	0.1	UJG03M22
UJSP25X12	12	25	56	28	13	0.16	UJG04M25
UJSP28X14	14	28	60	30	14	0.2	UJG05M28
UJSP32X16	16	32	68	34	16	0.3	UJG1M32
UJSP36X18	18	36	74	37	17	0.45	UJG2M36
UJSP42X20	20	42	82	41	18	0.6	UJG3M42
UJSP45X22	22	45	95	47.5	22	0.95	UJG4M45
UJSP50X25	25	50	108	54	26	1.2	UJG5M50

For further sizes please enquire  
 All dimensions in mm unless specified  
 If a dimension is critical to your application please contact our sales department for confirmation.  
 Please note : errors and omissions excepted.