

**Single Joint****Plain Bearings****UNBORED LONG****Type UJSPL in Steel**

UJSPL Properties		Further bore types as below available on request
Maximum working angle	45 degrees	
Maximum speed	1000 rpm	
Maximum power	6kW	
Maximum torque	600 Nm	
Higher power and torques are available using larger diameter or needle roller bearing joints : please enquire		
NB : It is recommended that all plain bearing joints should be used with a protective gaiter to assist lubrication and help arrest the ingress of dirt.		

Stock No	Bore	Diameter D	Overall length L2	Pivot centre L1	Hub length C	Weight KG	Gaiter type
UJSPL16XSOL	SOLID	16	56	28	19	-	UJG01M16
UJSPL22XSOL	SOLID	22	76	38	26	-	UJG03M22
UJSPL25XSOL	SOLID	25	86	43	28	-	UJG04M25
UJSPL28XSOL	SOLID	28	90	45	29	-	UJG05M28
UJSPL32XSOL	SOLID	32	95	47.5	29.5	-	UJG1M32
UJSPL36XSOL	SOLID	36	108	54	34	-	UJG2M36
UJSPL42XSOL	SOLID	42	127	63.5	40.5	-	UJG3M42
UJSPL45XSOL	SOLID	45	127	63.5	38	-	UJG4M45
UJSPL50XSOL	SOLID	50	140	70	42	-	UJG5M50
UJSPL58XSOL	SOLID	58	166	83	51	-	UJG5M58

For further sizes please enquire

All dimensions in mm unless specified

If a dimension is critical to your application please contact our sales department for confirmation.

Please note : errors and omissions excepted.