



## Single Row Angular Contact Ball Bearings Metric

Primary Dimensions			Bearing Code	Variants		
d	D	B		OPEN	ZZ	-2RS
mm						
10	26	8	7000	*		
	30	9	7200	*	*	*
	35	11	7300	*		
12	28	8	7001	*		
	32	10	7201	*	*	*
	37	12	7301	*		
15	32	9	7002	*		
	35	11	7202	*	*	*
	42	13	7302	*	*	*
17	35	10	7003	*		
	40	12	7203	*	*	*
	47	14	7303	*	*	*
20	42	12	7004	*	*	*
	47	14	7204	*	*	*
	52	15	7304	*	*	*
25	47	12	7005	*	*	*
	52	15	7205	*	*	*
	62	17	7305	*	*	*
30	55	13	7006	*	*	*
	62	16	7206	*	*	*
	72	19	7306	*	*	*
	90	23	7406	*		
35	62	14	7007	*	*	*
	72	17	7207	*	*	*
	80	21	7307	*	*	*
	100	25	7407	*		
40	68	15	7008	*	*	*
	80	18	7208	*	*	*
	90	23	7308	*	*	*
	110	27	7408	*		
45	75	16	7009	*		
	85	19	7209	*	*	*
	100	25	7309	*	*	*
	120	29	7409	*		
50	80	16	7010	*		
	90	20	7210	*	*	*

Primary Dimensions			Bearing Code	Variants		
d	D	B		OPEN	ZZ	-2RS
mm						
50	110	27	7310	*	*	*
	130	31	7410	*		
55	90	18	7011	*		
	100	21	7211	*	*	*
	120	29	7311	*	*	*
	140	33	7411	*		
60	95	18	7012	*		
	110	22	7212	*	*	*
	130	31	7313	*	*	*
	150	35	7412	*		
65	100	18	7013	*		
	120	23	7213	*	*	*
	140	33	7313	*	*	*
	160	37	7413	*		
70	110	20	7014	*		
	125	24	7214	*	*	*
	150	35	7314	*		*
	180	42	7414	*		
75	115	20	7015	*		
	130	25	7215	*		*
	160	37	7315	*		*
	190	45	7415	*		
80	125	22	7016	*		
	140	26	7216	*		*
	170	39	7316	*		*
85	130	22	7017	*		
	150	28	7217	*		*
	180	41	7317	*		
90	140	24	7018	*		
	160	30	7218	*		*
	190	43	7318	*		*
95	170	32	7219	*		
	200	45	7319	*		
100	180	34	7220	*		*
	215	47	7320	*		*

If a dimension is critical to your application please contact our sales department for confirmation.  
Please note : errors and omissions excepted.