

TYGRIS TECHNICAL DATA SHEET



Industrial Maintenance Aerosols

Heavy Duty Adhesive (Non-Chlorinated)

CODE: R260

High strength adhesive in non-chlorinated form

An easy to use, repositionable adhesive for bonding most surfaces, including textile, foam, rubber, plastic, foil, cardboard and paper. Good for fixing down carpets, underlay and floor tiles. In a non-chlorinated form for maximum safety.

Benefits: Strong, repositionable adhesion
Fast drying
Bonds most surfaces
Variable discharge fan nozzle
High strength bond

Technical Data:

Appearance: Yellowish fan of rapidly drying product
Odour: Typical glue/solvent odour
Contents: Blend of styrene butadiene polymer and supplementary additives in heptanes, acetone and butanone with butane/propane propellant
Storage: Below 50°C
Solubility: Insoluble in water
Flash Point: <0°C
Temperature range: Up to 50°C maximum surface temperature
Relative density: 0.84
Pack Sizes: 12 x 400ml cans. Variable fan nozzle
Directions for Use: Ensure surfaces are clean and dry. Shake can well before use. Spray a number of light coats. For maximum adhesion, cover both surfaces. Allow a few moments for solvent to evaporate, then press surfaces together firmly, working out from the centre. Clean off excess adhesive with a solvent. When finished, invert can and spray briefly to clear the nozzle.
Do not use when surface temperatures will exceed 50°C
Not for use on plasticised PVC
Use only in well-ventilated areas