


# TO PLACE AN ORDER CALL 01202 746031

TO RECEIVE EXCLUSIVE PRICE DISCOUNTS





**Automotive Brochure** 



# % 960400SP **VENOM Induction Heater** Deluxe Kit

 Generates Invisible Heat® to release corroded and thread locked metal components without the danger of an open flame.

1 KILOWATT INPUT - 1 KILOWATT OUTPUT

#### Features include:

- Angled Design with Trigger: Lightweight, ergonomic design allows for induction heat to access hard to reach places more easily.
- Coil Twist Lock: Coils now lock down with one simple turn (no more thumb screws)
- LED Usage Indicator: A red LED will light under fault conditions and green LED lights while the trigger is active and the tool is heating properly.
- Fault Override Delay: Any event that causes the red LED to illuminate will protect the tool by
- starting a three second lock out.
  Fan Operation Enhancements: The fan continues to run after the trigger is released to aid in thermal cycle time reduction and will stay powered when the thermal switch opens to aid in
- cooling the tool.

   User Controlled LED Switch: As long as the tool is powered and the internal power supply is operating, the LED will remain lit when the switch is on
- Three Year Limited Warranty.

THREE YEAR WARRANTY





# **Brake Pipe Flaring Tool Master Kit - Imperial** and Metric

SAE Single & Double Flares:
• 3/16", 1/4", 5/16", 3/8", 1/2", 4.75, 6, 8, 10 &

#### **DIN Single Flares:**

- 4.75mm
- Bench Mounted
- Produces both Convex and Double Lap flares to SAE and DIN standards
- Unique Dial-a-Size Turret design
- Lever cam operation for quick flaring
- Automatic punch extraction from flare
- Screw clamp for accurate die alignment



£349.00

# % 90206000

# ibro Impact Air Hammer

- A unique concept to aid the removal of seized suspension parts.
- The Vibro-Impact system allows for the controlled application of force via an air powered Impact
- Allows the operator to control and gradually increase the force being applied, in order to loosen seized components.
- Features a built-in shock-absorber in order to minimise risk of damage if too much pressure is accidentally applied. Low vibration for user comfort.
- Supplied with a handy wall mounted storage bracket and a set of four Impact Hammers for

#### Specifications:

- · Length: 290mm
- Air supply: 6.2bar (90psi)
- Air usage: 114 ltrs / min
- Stroke: 2200 bpmNoise level: 100dBA

£421.00

# % 902130SP

#### Micro Die Grinder & Bit Set

- The latest generation mini composite device for small / fine grinding and milling.
- Provides perfect handling due to the Bionigrip anti-slip surface.
- Minimal vibration and low noise.



- · Exhaust air through hose to the rear.
- 70,000rpm.
- Contains five shaped ends

£249.95

# **385801SP** Pneumatic Coil Spring Compressor

- Universal piece of equipment for assembling and disassembling struts and coil springs - suitable for Cars, 4WDs and LCV's.
- Automatic jaw levelling pivots to compensate and hold all coil springs including left hand coils.
- · Safety switch prevents operation when gates are open.
- Interchangeable jaws / vice to suit
- different springs. Up to 2452kg of force (at 8 bar) at the touch of a pedal.
- Full height steel safety gates.
- Top arms and jaws adjust and lock to secure spring.
- Unique double depth front plate allows safe work on extra long strut assemblies.
- 4 x 10mm floor mounting holes for
- insurance company compliance.
   Safety cut-out for de-activation of cylinder when safety guard is opened.
- Also Includes: GO338- Upper Bracket for Spring Compressor.

#### Contents:

- Bracket A: 78 " 130mm (38481200) • Bracket C: 105 - 182mm
- (38481400)
- Strut Vice
- Safety Guards



@Svi




#### Specifications:

- Dimensions: 1600x520x300mm
- Working Pressure: 8 bar (116 psi)
- Compression Force: 2452 kg (24500N)
- Cylinder Stroke: 330mm
- CE approved

£2395.00

# **%** GO338 **Upper Bracket for** Spring Compressor




Coil Spring Compressor. The bracket is able to adapt to a vast number of applications since it is equipped with a rotating and universal plate with fixing holes and slots.

The design is ideal for;

- Springs with a small number of coils; meaning that one more coil
- can always be tensioned automatically.
- Simplifying dismantling and assembly operations.
  The rotatable and fixable mounting plate is provided with a
- universal hole division. In addition, the holder between the arms can easily be tilted.

£560.40

# **30047500** Wireless Electronic Stethoscope Kit -"Chassisear"



Can be used on cars, vans, trucks, buses etc as there are no cable length issues to overcome.

- Consists of Receiver Unit, 4 x Transmitter Units (4 channels), 4 pick-up leads, pick-up fixing straps, headphones, batteries, instruction manual & storage case.
- Pick-up clamps can be attached to many different parts of the vehicle in order to amplify the sounds made under load and in actual driving conditions.

N.B. Due care and consideration should be taken of driving conditions & regu operating the Chassisear on the road. £569.00

# **Automotive Broch**

01202 746031

# **%** GO434SP ord Ecoblue Injector Removal Set

- Set of special tools to remove the injector on Ford Eco Blue vehicles.
- Provides removal of heavily seized injectors in a professional, safe and
- Non-seized injectors can be removed using the fork and reused as required.
- Includes tools for extraction of injectors in single parts if broken.

- · Complete extraction of non-seized injectors with a special fork.
- Advantage: It is not necessary to replace the injector; it can be reused.
  Partial extraction of injector with special tools included in the set.

# Special Offer - Free GO519 Injector Removal Socket with the purchase of this product, worth - £60

Special socket for the removal of injectors

Engine codes:
• YLFS, YLF6, YMF5, YMF6, YNF5, YNF6, YLR6, YMR6, YNR6



£698.80

# **%** GO030 en2 Wheel Bearing Naster Kit 62-85mm

- Full assortment for correct removal and installation of gen2 bearing hub units on vehicles ranging from passenger cars to transporters
- The perfect set for all current bearing units
- The perfect set for an content bedaing units with diameters of 62 85 mm.
  Includes a threaded spindle M20 and nut, and a counter-pressure nut with pressure bearing for mechanical operation. For frequent use with large bearing units or badly corroded bearings, we recommend the optional 12-tonne hydraulic cylinder (GO1012).
  The special half shells grip behind the wheel hub during installation and press on the snap ring located directly on the bearing outer ring. This prevents
- damage to the bearing and allows the snap ring to engage evenly.
- The repair work can be performed directly on the vehicle.
- Easy to use significant time savings no damage to the bearing.
   Sizes and assignment of half shell sets (HSS).

- 1 x HSS size 1 for Ø 62 mm • 1 x HSS size 2 for Ø 66, 68 mm
- 1 x HSS size 3 for Ø 72, 75, 78 mm
- 1 x HSS size 4 for Ø 82, 85 mm

#### Removal:

• 1 x HSS for Ø 62, 66, 68, 72, 75, 78, 82, 85 mm

£1399.00

# **≪** GO068 ■ Drive Shaft Disassembly Tool

- It is possible to remove the drive shaft inserted in the gearbox, with the use of this tool.
- Insert the tool between the drive shaft and gearbox. Then, with a slight slide
- hammer hit, the fixing circlip, found in the gearbox, is broken.

   The difficult position of the fixing circlip is avoided by the forks central traction. allowing the user to easily unblock the drive shaft.

£249.95

# **%** GO563

# Injector Extractor- Bosch M18 $\times$ 1.5

- Complete tool for the removal of Bosch magnetic injectors. The half-shells of the tool head are positioned directly
- under the screw ring of the injector electrical connection. The locking sleeve with window provides a non-slip grip.

  Removal is carried out without partial disassembly and this
- ensures that the injector can be reused. Connection internal thread M18x1.5

£339.95



# Mechadraulic Cylinder Adaptor Kit Thanks to the use of aluminium, the cylinder combines the

- strength of steel with the light weight of this element.
- Non-slip grip handle with 12T of force.
  There are 4 bores on the body for fastening the cylinder.
- Applications include: injector removal; installation of wheel hubs; general use in the loosening of very tight mechanical components.
- Adaptors: M10/M12/M14/M16/M18



£606.10

## **GO414** Injector Extraction Mech Basic Kil

 This set is required as a base for traditional injector removal tools, such as the slide hammer or hydraulic cylinder.

It contains all the tools needed to breakdown the injector and adapters to connect to injectors.

• The injectors can then be extracted with high impact and hydraulic forces.

• The set allows you to extract about 90% of all injectors.

£1036.90

C.O.O.

0000

000

## **%** GO1310 **HGV Split Bush Master Kit**

- Use this tool kit to remove and refit slotted bushes properly. The slight conical grinding makes it possible to extract and reuse bushes without damage.
- The tools can be fitted directly on the vehicle without removing entire axle components. Pieces may also be used on the workshop
- By using the locking device and relating half-shells, bushes are pre-tensioned carefully

and parallel to one another so they can be pressed easily into their seat. While the bush is often damaged using commercial tapered sockets, the assembly operations do not damage/deform/detach from the bearing's cover when this

- locking device system is used.

   The half-shells are fixed securely inside the locking device so they will not slip
- The kit includes a wide selection of the most common applications with high market coverage. Other half-shell kits will soon follow to ensure the subsequent removal of the system
- Due to the extremly high forces required for removal, the use of a hydraulic cylinder is recommended. The Govoni 12-ton hydraulic cylinder is therefore optimal for integrations (See kit GO1310R to purchase with the GO1012 Hydraulic Cylinder)

#### **Applications**:

- Ø 75mm MB Actros (stabilizer) Ø 70mm MAN
- Ø 68mm MAN (front spring) ROR, SAF
- Ø 66mm IVECO Eurostar (driver's cabin)
- Ø 65mm MB Actros (stabilizer), Atego
- Ø 63mm DAF
- Ø 60mm MB/IVECO Eurostar (stabilizer), Renault Kerax, Magnum, Premium
- (leaf spring eye) Ø 58mm MB 3229 B, 652, 650/Volvo
- Ø 56mm IVECO SAVING: £250.00 Eurostar (driver's
- £999.00 cabin)

# **%** GO700

# ockets for NOX and Particulate Sensors

- Allows professional disassembly and assembly of exhaust particle NOX sensors.
- The closed 6-point profile allows for very high loosening torques, especially with an extremely locked coupling.
- The special design of the socket wrench prevents slipping and damage of the socket profile on the
- The connection cable is lead to the side of the socket and is therefore protected from cuts and incisions.

#### Components:

- 1 x 24mm Socket
- 1 x 32mm Socket

Technical data:
• Total length 85 mm

- 1 x 19mm Socket Adapter
- 1 x 17mm Socket Adapter

• 1/2" guide

• 1 x 14mm Socket Adapter

• 1 x 24mm Socket Adapter

x 22mm Socket Adapter

£365.00

# **GO451**

## **Universal Glow Plug Tip** Extraction Set

- Universal Glow Plug Tip Extraction Set -Master M8X1-M9X1-M10X1-M10X1,25.
- **Double Pulling System** For the extraction of the electrode terminal part of
- the glow plugs (M8, M9, M10) in the event of breakage or sticking inside the seat port, which is otherwise impossible to remove. • The set includes all the tools needed to safely remove the terminal part of the
- glow plug electrode without damaging the cylinder head
- This operation can be completed with a slide hammer or threaded extractor.

£564.90

# \$\sqrt{80062000}\$ Gear Belt Installation/Removal Tool-

• Special tool to aid in the removal & installation of gear belts where a torque multiplier is required.

- Torque Multiplier 1/2" Sq Drive Input, 3/4" drive Output
- Securing bracket & fixings
- · Supplied in a storage case with foam

**Applications:** 

Ford EcoBoost



£425.00

# % 343001V2

# 12v Automatic Brake Bleeder

- Updated Model Now includes regulator from 0 to 6 bar and 4 x wheels (2 x front swivel).
- Allows one man operation for brake and clutch bleeding.
  Compatible with ABS systems.
- 12v powering with reverse polarity warning.
  Stainless steel body.
- Includes pump with automatic shut off valve.
- 5L reservoir with visible (min) level indication.
- Auto power OFF when min level reached.
- Large reservoir opening for easy cleaning
- Includes aluminium SP Euro cap angled screw type.
  Power cable for brake fluid with quick coupling system



£975.00

# **%** 53400800

### Smoke Diagnostic Machine

Generates a thick and highly visible smoke with multiple adaptors to help connect the product to most vehicles.

#### **Specifications:**

- Rated Voltage: DC12V
- Rated Power: 100W
- Smoke Output: 20-30L/MIN
- Working pressure: 1.3 Bar Delivery (0-18PSI)

#### Includes:

- Smoke Leak Detector
- Valve CoreSmoke Pipe

- Universal Inflatable Adapter
  One large, medium and small taper
- 250ml bottle of smoke oil



£495.00

# **34400500**

## 240v Electric Brake Bleeder - 4 Bar

- Allows one man operation for brake and clutch bleeding.
   Compatible with ABS systems.
- Rugged impact resistant moulded housing.
- Long supply hose (3.2 metres) allows for use with vehicle raised on a ramp.
- Adjustable pressure output from 0 4 bar to suit the vehicle.
- Large internal storage area for brake fluid containers up to 10
- Includes 34301400 aluminium SP Euro cap angled screw type for popular vehicle connection.

  • Additional range of caps also available.
- Maximum Pressure: 4 bar.
- · Weight: 10kg.



**SAVING: £50.00** 

# £575.00

# % 53380000

#### 80L Air Operated Oil Extractor

- Pneumatic Oil Extractor for fast recovery of engine oil from any vehicle.
- Extraction takes place from the engine sump with oil at 66° C.
- Includes six probes for extraction.
- Visual indicator of oil for ease of use
- Includes pressure safety valve set at 7.2 bar.

- Carbon steel reservoirEpoxy coated finish
- Pneumatic emptying
- Drain plug for cleaning and internal inspection
- · Drain bowl with drain filter grid

#### Technical Specifications:

- Width: 540mm
- Depth: 620mm
- Height: 1250mm
- Bowl Height (from Reservoir): 580mm

Includes 4 quick-fit adaptors for models with integrated suction tubes;


- MercedesBMW
- Volkswagen
- PSA

£389.00

# % 02688000 **MOT Approved Headlight Beam**

- Tester HGV
- Mechanical Headlight Beam Testers MOT Approved.
   Features rotating column with adjustable mirror visor for accurate alignment to vehicle.
- Luxmeter with graduated analogue scale for accurate light intensity measurement.
- Easily adjustable vertical sliding mechanism by self lubricating sliders.
- Features built in MOT beam checking panel.
- Suitable for all headlight types including Xenon.
  5.2 metre rail kit / column height: 1.66m.
- Base mounted on double rail for ease of use (self install only)
- Includes a kit to make 2 x 5.2 metre rails (6 x 1.50m + 2 x 0.70m)

£879.00



#### Brake Bleeder Cap-Starter Set • Starter cap bleeder set suitable for '343' & '344' Range of

- Brake Bleeders. Precision engineered aluminium caps for the following applications:
- 34301000 Ford Fiesta
   34301100 Nissan / Asian (Bayonet Type Cap)
   34301500 Euro Cap (Screw Type Cap)

£165.00

# % 34305000

#### **Brake Bleeder Cap Set** Suitable for '343' & '344' range of

- brake bleeders
- 34301000 Ford Fiesta Cap
- 34301100 Nissan / Asian Cap
- 34301200 Pixo / Matiz Cap 34301300 Micra Cap
- 34301500 Euro Standard Cap



£279.00

# **%** 53380500

## **80L Air Operated Oil Extractor with** Viewing Chamber

- Pneumatic Oil Extractor for fast recovery of engine oil from any vehicle.
- $\bullet$  Extraction takes place from the engine sump with oil at 66° C.
- Includes six probes for extraction. • Visual indicator of oil for ease of use · Includes pressure safety valve set at 7.2 bar.

#### Features:

- Carbon steel reservoir
- Pneumatic emptying
  Drain plug for cleaning and internal inspection
- Drain bowl with drain filter grid



- Width: 540mm
- Depth: 620mm
- Height: 1250mm
- · Bowl Height (from Reservoir): 580mm

Includes 4 quick-fit adaptors for models with integrated suction tubes; MercedesBMW Volkswagen

- PSA

£499.00

01202 746031



# % 31470000

Oil Pressure Test Kit

- Helps to diagnose worn oil pumps and engines, faulty oil pressure switches and pressure warning indicators.
- Shock protected dual scale gauge, for quick and accurate oil pressure checks.
- Permanently oil primed, long flexible hose, enables access to difficult to reach oil switch ports.
- Small profile, quick coupling adaptors with built-in shut-off valve for a fast and secure connection.
- Includes oil pressure test gauge c/w 1m oil primed hose and 10 x oil switch port adaptors
- Supplied in plastic case with foam insert.

#### Specification:

- New M12 x 1.75mm adaptor available to suit engines commonly found on newer GM, Vauxhall & Opel models 31472270
- 1m flexible oil primed hose
- Gauge Scale 0 10bar, 0 150psi
- Gauge Diameter: 80mm
   Gauge to DIN16005, DIN16063, BS1780 standards

£259.95

#### Unbreakable\* Vice - Fixed Base

- High quality, heavy duty construction provides years of trouble free use.
- CNC machined components for excellent fit and durability.
- Hardened and tempered finely ground jaws for superior grip.
   Scratch resistant hammered blue finish.
- \*Excluding jaws and handles replacements available

| PART NO  | SIZE (INCH) | PRICE                    |
|----------|-------------|--------------------------|
| 53320400 | 4"          | £72.95                   |
| 53320600 | 6"          | £112.95                  |
| 53320800 | 8"          | £155.00<br>SAVING: E8.95 |



#### Swivel Base for Unbreakable Vice

- Allows 360° rotation of Mechanics Vice for better access.
- Lockable to most convenient angle.

| PART NO  | SIZE (INCH) | PRICE  |
|----------|-------------|--|
| 533204-В | 4"          | £11.95   |
| 533206-В | 6"          | £18.95   |
| 533208-В | 8"          | £21.50   |
|          |             | and the same of th |



# % 33100100 Diesel High Pressure Kit

- For use with 33100000 Universal Digital Pressure Tester - Comprehensive Kit
- Easily and safely test the diesel common rail pressure.
   Safely test the diesel common rail pressure, both in line
- (in series with engine running) and for direct pump pressure (cranking the engine).
- Instead of the pressure information provided by the car's sensor that may have an issue, this set provides all hardware (special sensor, plugs, hoses) to perform a precise and accurate test when used with the 33100000 Digital Pressure Tester-
- The hoses included in the set will allow measurement and diagnosis on most usual common rail engines. £499.00

# **33100500**

- For use with 33100000.
- Kit includes 8 different dummy to seal any regulator ports.
- This set, when used with 33100100, will allow bypass of the pumps regulator and measure the pressure to diagnose any regulator or pump issue





- Common Rail Cap Set

  When used with the 33100100, this set will allow closure of fuel inlet injectors directly on the common rail to identify whether an injector is leaking or not.

  • Works for 3, 4, 5 & 6 cylinder engines.
- 6 x M12x150 plugs
- 6 x M14x150 plugs

£62.95

# **331595V3**

## 315' Series Cooling System Pressure **Test Kit**

- Provides an effective solution when pressure testing the cooling system to help locate internal and external leaks.
- Updated kit now includes caps to cover the latest applications for Vauxhall / Saab and BMW / Mini vehicles.
- Suitable for modern vehicles with in-built overflow at the top of expansion tank.

- Hand Pump with Pressure Gauge & Quick-Release fitting
- Hose Assembly c/w quick-release fitting
- 16 x Threaded cap adaptors
- 3 x Bayonet Fitting cap adaptors
- 1 x Cap Adaptor wrench

- Applications include:
   Vauxhall: Adam, Astra J, Cascade, Corsa E, Meriva B, Mokka & Zafira Tourer C • Saab: 9-5 2010-
- \* Sddb. 7-5 2010-\* BMW 4.4.8/6.0 engines: 5 Series (F07/10/11) 2010-, 6 Series (F06/ F12/13) 2011-, 7 Series (F01/02/03) 2009-, X5 (E70) 2008-,X6 (E71/E72)
- 2008 and BMW i3 2013-Mini models: F54, F55, F56, F57, R50, R52, R53, R56, R57, R58, R59 & R60



£345.95

# **%** 08070000 **HGV Ball Joint Separator**

- Strong, heavy duty body, with strengthened fork and lever, allows for greater force to be applied.
- Can be upgraded to hydraulic power (use 08075000 Upgrade Kit).

- Jaw Opening: 70mm Jaw Throat Width: 36mm
- Jaw Throat Depth: 50mm

£162.95

# **%** 33100000 **Universal Digital Pressure Tester -**Comprehensive Kit

• Ad Blue Pressure

• Fuel Low Pressure

Vacuum Pressure

• Particle Filter Pressure

- Universal Digital Pressure Tester full kit for standalone
- use all possible applications.

   Save, export, print and share results for selected applications

#### Possible Applications:

- Compression Petrol/ Diesel
- Oil Pressure\*\*
- Turbo Pressure
- Cooling System Pressure

#### **Full Kit Contents:**

- Sensor 0 to 300Bars
- Sensor 1 > 3Bars

- Universal Diesel Compression Adaptor
   Universal Petrol Compression Adaptor
   Eight specific professional quick coupling adaptors
- Vacuum adaptors
- \*\*Adaptors required for entry via oil pressure sensor.



£1599.00

## **%** 33100300 Petrol High Pressure **Adaptors**

- For use with 33100000.
  Use this kit with the 0-300 bar sensor included in kit, 33100000, to test the high pressure of most popular petrol

#### Kit includes: • HP1 = M12x150 • HP2 = M12x125

- HP3 = M14x150
- HP4 = M10x100 HP5 = M8x100
- £114.00

# **33100700** Diesel High Pressure Adaptors

- For use with 33100000.
- When used with the 33100100 Diesel High Pressure Kit, the diesel high pressure of most popular cars on the market can be tested.
- All adaptors feature a M12 x 150 thread, the others ends are as follows;
  • M12x125 (2x)
  • M14x150 (2x)

- M14x100 (1x)
- M16x100 (1x)

£415.00

# **%** 341400SP galithium Booster 12/24V

 The lithium booster is a powerful and ultra-light booster for professional use - The GIGALITHIUM boosters is suitable for difficult starting vehicles to start but can also be used to protect/remember the memory of vehicles.

Longer life span, no maintenance, extremely safe lightweight, improved discharge and charge efficiency.

#### **Specifications**:

- Operating Voltage: 12/24V
  Continuous Current: 2000/1000A
- Start Max Ampertage: 5000/2500A
- Peak Amp: 10000/5000AClamp Output: 1000A
- Cable Length: 160cm

- Cable Size: 25mm
  Maximum Charge Voltage: 14.5V
  Automatic Battery Charger: 14.5V
- Battery Type 2 Pack Lithium: LiFePo4
- Reverse Polarity Protection: Yes
- Short Circuit Protection: Yes
- Overvoltage Protection: Yes
- Memory Saver: YesDimensions: 350 x 240 x 140

## **%** 341200SP Gigalithium Booster 12V

The Giga Lithium booster 12V can handle all vehicle using a 12V battery and with up to 40 starts on a charge.

- Specificactions:
   4 cells Lithium LiFePO4 battery 100% safe
- Cranking Amps: 800CA
- LCD Screen
- Microprocessor controller
- Reverse Polarity Protection: Yes
- Short Circuit Protection: Yes
- Overvoltage Protection: Yes
- Memory Saver: Yes
- Protection again over discharge
- Protection against over charge
- Protection against over temperature
- Over ride mode
- Cable Length: 50cmCable Size: 10mm



# % 03204500

## V/24V Battery Tester & Printer

- Designed for 12V & 24V battery, starter, alternator and ground tests.
   Compatible with WET, AGM, EFB, GEL, SPIRAL batteries.

- Features an integrated thermal printer (+ 1 spare paper roll).
  Equipped with a full colour interface, LCD display, touchpad with sensor technology.
- Offers the possibility to type in the customers details.
- Supplied with a SD Memory card for storing the test reports
- A QR code is printed with each test report. Simply scan it to share the test results.
  New added function: keeps track of how many tests are done daily for each test
- Optional cigarette lighter socket cable to test the alternator directly through the 12V plug of a vehicle.



£369.00

## **Battery Chargers**

- Designed to charge and maintain and recover all types of lead-acid batteries.
- The intelligent charging process allows the charger to be left permanently and safely connected to a battery to provide continuous maintenance once charged.
   The charger comes with three charging accessories: clamps, eyelets and cigarette lighter connector.
- ullet An easy to read display with LED's shows the charging status in % as well as the selected mode.

| PART NO     | CHARGING<br>CAPACITY               | MAINTENANCE<br>CAPACITY | CABLE LENGTH | DIMENSIONS        | WEIGHT | PRICE   |
|-------------|------------------------------------|-------------------------|--------------|-------------------|--------|---------|
| 896122425SP | 50-450Ah (12V) /<br>25-230Ah (24V) | Up to 500Ah             | 187cm        | 29 x 12 x 7cm     | 2.2kg  | £244.95 |
| 89612247SP  | 14-150Ah (12v) /<br>14-75Ah (24V)  | Yp to 225Ah             | 180cm        | 206 x 88.5 x 52mm | 0.7kg  | £85.50  |
| 8961238SP   | 1.2-14Ah (6V) /<br>1.2-75Ah (12V)  | Up to 120Ah             | 180cm        | 175 x 65 x 43.5mm | 0.46kg | £64.95  |

| PART NO   | INPUT                   | POWER | BATTERY<br>CAPACITY               | CABLE LENGTH | DIMENSIONS      | PRICE  |
|-----------|-------------------------|-------|-----------------------------------|--------------|-----------------|--------|
| 8961211SP | 220-240VAC -<br>50/60HZ | 30W   | 2.2-40AH (6V) /<br>2.2-40AH (12V) | 180cm        | 153 x 59 x 38mm | £53.95 |











8961211SP

## SPEEDLINE3100 Booster Pack 12V AGM

#### Specifications:

- Voltage 12V
- Battery Capacity- 25AH
  Cranking Amps / Peak Amps -1200 CA/ 3100 PA
- Cable length / cross-section- 70 cm / 25mm²
   Automatic charger -12V-2A
   Clamps full insulated -brass clamps

- Cigarette-lighter socket included
- Short-circuit protection fuse- 300A Fuse Built in clamp



£399.00

## SPEEDLINE3200 Booster Pack 12V AGM

#### Specifications:

- Voltage 12V
- Battery Capacity- 25AH
   Cranking Amps / Peak Amps -1200 CA/ 3100 PA
- Cable length / cross-section- 84CM/25MM²
   Automatic charger -12V-2A
   Clamps full insulated -brass clamps

- Cigarette-lighter socket included
- Short-circuit protection fuse- 300A Fuse Built in clamp

£599.00

# SPEEDLINE5000 Booster Pack 12/24V AGM

#### Specificactions:

- Voltage- 12/24V
  Battery Capacity- 2 x 22Ah
  2000/1000 CA 5000/2500 PA
  Cable length / cross-section- 130 cm / 50mm²
  Automatic charger- 12V-3A
- Clamps- Fully insulated brass clamps
- Cigarette-lighter socket- Included
   Short-circuit protection fuse- 500A fuse built in clamp
- Voltmeter- Colour-coded LEDs (battery level + alternator status)



£849.00

# SPEEDLINE6200 **Booster Pack with Trolley** 12/24V AGM

#### Specifications:

- Voltage- 12/24V
- Battery Capacity- 2 x 25Ah
  Cable length / cross-section- 155 cm / 50mm²
- Automatic charger- 12V-3A
- Clamp- Fully insulated brass clamps
- Ciaarette-liahter socket- Included • 2400/1200 CA - 6200/3100 PA
- Short-circuit protection fuse- 500A fuse built in clamp



£999.00

#### Motorq Split Torque Wrenches

- Split Torque Design The new generation design can be split into two parts for easy and economic storage and shipping.
- New Torque Scale.
- Push-through ratchet allows two directional torquing.
- Robust construction gives accurate results to ±4% even in arduous working conditions.
   Tool is supplied with a Declaration of Conformance which meets the requirements of ISO 6789-1:2017.
- Unique profiled cam ad reaction plate gives much clearer torque signal and the large break angle greatly reduces the possibility of over torquing.
- Designed to be cost effectively serviced.
- New handle more comfortable and guides operators hand to correct position.
   Easy to read scale is shielded from dust, dirt and spray.
- Easy to set accurately setting tool included.

| DARTNO   | DESCRIPTION               | CALIBRAT | PRICE   |         |  |
|----------|---------------------------|----------|---------|---------|--|
| PART NO  | DESCRIPTION               | N-M      | LBF-FT  | PRICE   |  |
| 80240000 | 3/4" Sq. Dr               | 200-800  | 150-600 | £598.00 |  |
| 80250000 | 3/4" Sq. Dr               | 300-1000 | 200-750 | £615.00 |  |
| 80250500 | Stepped 3/4" to 1" Sq. Dr | 300-1000 | 200-75  | £640.00 |  |



#### Motorg Push-Thru Professional Torque Wrenches

- Accurate to +/-3% of reading which meets the requirements of ISO 6789-2:2017.
   Supplied with a traceable calibration Certificate allowing end-users to adhere to more stringent quality control processes.
- 60% larger scale for better visibility and improved accurate setting.
- Scale adjusts 40% faster but the effort required to adjust is reduced.
   Improved serviceability means longer life and reduced ownership costs.
- Superior, ergonomic handle and shape Soft-feel, high grip material and more comfortable
- Now includes a push/pull type lock Faster use and the coloured band on the lock clearly shows that the wrench is unlocked.
- New Timestrip® Feature Timestrip® provides a visual indication that the wrench is due for re-calibration and has 3, 6, 9 and 12 month graduations.

| DART NO  | DESCRIPTION    | CALIBRAT | PRICE    |         |
|----------|----------------|----------|----------|---------|
| PART NO  | DESCRIPTION    | N-M      | LBF-FT   | PRICE   |
| 80105000 | 3/8" Push Thru | 10-50    | 7.5-37.5 | £199.00 |
| 80110000 | 1/2" Push Thru | 20-100   | 15-75    | £190.00 |
| 80120000 | 1/2" Push Thru | 40-200   | 30-150   | £207.00 |
| 80130000 | 1/2" Push Thru | 60-300   | 50-220   | £233.00 |
| 80134000 | 1/2" Push Thru | 60-340   | 50-250   | £249.00 |
| 80140000 | 3/4" Push Thru | 80-400   | 60-300   | £349.00 |



## **SPEEDLINE Torque Wrenches**

- Accurate to ±3% of reading which meets and exceeds ISO6789:2003.
- Light and fast adjustment saves operator time and effort.
- Micrometer scale applying to the primary torque units (N.m on a dual scale wrench) for simple and error free setting.
- Push through ratchets allow torque control in both the clockwise and anti-clockwise directions
- Tough ratchets with narrow engagement angles allow for easy positioning of the tool in confined spaces. 5° for models up to 200 N.m and 6° for models 300 N.m and above
- Pull/push lock is fast and intuitive to use and prevents accidental adjustment of the set
- Convenient hanger feature for tool storage also aids wrench unlocking and adjustment.

| PART NO      | DESCRIPTION    | CALIBRAT | DDIGE  |         |
|--------------|----------------|----------|--------|---------|
|              | DESCRIPTION    | N-M      | LBF-FT | PRICE   |
| SPEEDLINE60  | 3/8" Push Thru | 12-60    | 10-45  | £153.00 |
| SPEEDLINE100 | 1/2" Push Thru | 20-100   | 15-75  | £159.00 |
| SPEEDLINE200 | 1/2" Push Thru | 40-200   | 30-150 | £169.00 |
| SPEEDLINE300 | 1/2" Push Thru | 60-300   | 45-220 | £178.00 |
| SPEEDLINE340 | 1/2" Push Thru | 60-340   | 50-250 | £195.00 |



SPEEDLINE 60



SPEEDLINE 100



SPEEDLINE200



SPEEDLINE300

(a) ↑ (b) — (c) × (d) SPEEDLINE340

#### Evotorque® Battery Tool

- The EvoTorque® Battery Tool (EBT) is a fast, reliable and accurate battery torque tool which features a brushless motor, data memory and data transfer capabilities.
- Test and record the torque on every bolt.
  Keep full electronic records for your fleet

| PART NO | DESCRIPTION  | SQ<br>DRIVE | CALIBRATED<br>RANGE | TOOL WEIGHT* | REACTION<br>WEIGHT | OUTPUT SPEED | PRICE      |  |  |  |
|---------|--------------|-------------|---------------------|--------------|--------------------|--------------|------------|--|--|--|
| 180349  | Single Speed | 3/4"        | 100-800nm           | 6.2kg        | 3.7kg              | 11.2rpm      | £8,008.24  |  |  |  |
| 180541  | EBT-92-4000  | 1"          | 400-2700nm          | 5.9kg        | 1.4kg              | 3.3rpm       | £8,774.10  |  |  |  |
| 180637  | EBT-80-2700  | 1"          | 800-4000nm          | 7.9kg        | 2.5kg              | 2.3rpm       | £9,016.15  |  |  |  |
| 180469  | Auto 2 Speed | 1"          | 338-1350nm          | 6.2kg        | 1.4kg              | 32rpm        | £9,277.41  |  |  |  |
| 180565  | Auto 2 Speed | 1"          | 400-2700nm          | 6.5kg        | 1.4kg              | 13rpm        | £9,840.92  |  |  |  |
| 180661  | Auto 2 Speed | 1"          | 800-400nm           | 8.5kg        | 2.5kg              | 9.5rpm       | £10,082.98 |  |  |  |



# **%** 21027500

# **HGV Hub Puller Kit**

- Variable for pitch circle diameter up to 445mm.
- To suit wheel stud sizes commonly found on DAF, MAN, MERC, RENAULT, SCANIA & **VOLVO** models.

# Contains 5 x thread

- adaptor pairs; M18 x P1.5 x 65mm/L M20 x P1.5 x 65mm/L
- M22 x P1.5 x 65mm/L 7/8" 11 BSF
- 7/8" 14 UNF



£745.00

# **331400V2**

#### Cooling System Pressure Test Kit

Updated kit now includes additional caps. Contents:

- 10 x Reservoir & Radiator Pressure Caps
- High capacity metal bodied hand pumpQuick-Connect Hose Assembly
- Dual Gauge measures both p.s.i (0-35) and bar (0-2.5)

Additional Pressure Caps available - refer to applications guide

Applications include:
• DAF / Iveco / MAN / Mercedes / Renault / Scania / Volvo plus wide ranging coverage for Plant / Construction / Military & Agricultural solutions

£319.95

# **33145500**

#### Combustion Leakage Tester-HGV

- Quick test combustion leakage tester.
- Fast and accurate diagnosis of cylinder head gasket leaks.
- Suitable for use with both petrol
- & diesel HGV engines.
   Supplied with standard and sensitive reaction test fluid (100ml).
- 25 to 50mm cone.

£119.95



## 120L Oil Extractor with Under-Vehicle Tray

- Pneumatic equipment for fast recovery of engine oil from any vehicles. The oil change may take place by gravity, or by aspiration from the engine sump, with hot oil  $(70/80 \,^{\circ} \,^{\circ} \,^{\circ} \,^{\circ})$  through one of the 6 included probes. Simple to use, the equipment is provided with a pressure relief valve set at 4 bar. The device is manufactured in compliance with EC rules.
- Carbon Steel Reservoir
- Epoxy Coated Finish Pneumatic Extraction
- Drain plug for cleaning and internal inspection
- Metal drip tray with drain fiter grid

#### Technical Specification

- Tray 51L
- Air Inlet Connection 1/4
- Air Consumption 200 l/min
  Noise level <80 (dB)</li>
- Weight 83kg
- Reservoir Operating Pressure 4 bar
   Capacity 120l



£899.00

#### Pit Bridges

- Adjustable width, making it suitable for most pit distances.
- Technical Information:
- Width: 870-1150mm
- Loading Capacity: 400kg

Available with and without handrail







| PART NO. | DESCRIPTION                  | PRICE   |
|----------|------------------------------|---------|
| 51050500 | Flat Type - with Handrail    | £795.00 |
| 51060500 | Rail Type - with Handrail    | £799.00 |
| 51050000 | Flat Type - without Handrail | £599.00 |
| 51060000 | Rail Type - without Handrail | £589.00 |

# % 53401300

#### Coolant Flush Machine

- Dual-manual valve design, easy operation.
- Directly connect shop air, zero failure.
   Whole work process visible through fibre glass tanks
   Support off/on-vehicle exchange.
- Full coverage adaptors (covering more than 90% vehicles on the market.

#### Specifications:

- New and used oil capacity: 15L
- Pressure gauge: -1-5 bar
  Max. work pressure: 3 bar
- Length of return/out hose: 3m
- · Coolant hoses: 25mm, 32mm, 38mm, 42mm, 45mm, 60mm, 67mm

- Used fluid extraction Vacuum
- Add new fluid
- Empty new/used fluid tank



795.00

# **%** 53407500

#### **Ecomax Dual Service Equipment**

- A 6 in 1 cleaning system that removes problematic deposits from combustion chambers, injectors, throttle body, inlet valves, EGR, manifolds and DPF.
- Effective cleaning for petrol and diesel engines, eliminating the need for injector removal. The Injector Max system cleans and restores original fuel flow, allowing maximum fuel efficiency.

- Dual Tank Avoids cross contamination of fluids.
- Robust and reliable workshop quality machine
- Air operated and simple to use
- Universal fitting kit
- Suitable for petrol and diesel engines
- Fluids premixed and ready to use

#### After Service Benefits

- Cleans DPF and Catalytic filters on vehicles
- Reduces exhaust emissions
- Restores fuel economy and engine performance
- Removes carbon deposits
- Cleans injectors



5.00

#### KM Sockets and Extension Tube Kits

- Designed for easy tightening and loosening of locknuts
- They are used to secure and adjust bearings on tapered journals, adapter
- sleeves and withdrawal sleeves.
  Easy mounting and dismounting without nut damage.
- The socket demands less space around the bearing arrangement than when using a hook spanner and allows the use of ratchets and torque wrenches via a 1/2" drive.

| PART NO  | DESCRIPTION                                 | KIT INCLUDES | PRICE   |
|----------|---|--------------|---------|
| 69680000 | KM Socket Set                               | KM 4 - KM 10 | £259.00 |
| 69680100 | KM socket & Extension Tube Set              | KM 4 - KM 7  | £299.00 |
| 69680200 | KM Socket & Extensions Tube<br>Complete Set | KM 4 - KM 10 | £599.00 |



## **Hub Socket Range**

- Vehicle Applications Include:
- Scania Iveco
- DAF • MAN
- Renauli
- VolvoFiat
- Mercedes • BPW Fruehauf
- R.O.R • TGA



















FOR FULL RANGE VISIT: WWW.SYKES-PICKAVANT.COM

#### 'Silver Series' Hydraulic Workshop Presses

• NEW Silver Series range of Hydraulic Workshop Presses equipped with a two-speed manual pump, overload safety valve, automatic ram back-run system and V blocks.

#### Specifications:


- Heavy duty steel frame
- Automatic ram return
- Manufactured in the EU
- Two speed pump
- Pressure gauge
- Fully adjustable horizontal ram movement
- Piston over-travel limit stop
- · Delivered ready for use
- Overload safety valve
- V blocks
- New gauge position to enable easy
- Winch for table<sup>3</sup>

#### 15T, 20T, 30T & 50T rated models available

| PART NO. | RATING | HEIGHT<br>(MM) | WIDTH<br>(MM) | DEPTH<br>(MM) | BED<br>DEPTH<br>(MM) | RANGE      | WEIGHT<br>(KG) | PRICE    |
|----------|--------|----------------|---------------|---------------|----------------------|------------|----------------|----------|
| 53436010 | 15T    | 1930           | 920           | 650           | 170                  | 85 - 950   | 150            | £925.00  |
| 53436210 | 20T    | 2030           | 940           | 650           | 170                  | 65 - 1030  | 165            | £999.00  |
| 53436410 | 30T    | 2060           | 1120          | 650           | 200                  | 115 - 1020 | 230            | £1599.00 |
| 53436510 | 50T    | 2290           | 1220          | 650           | 210                  | 70 - 1065  | 370            | £2649.00 |

N.B. A standard delivery charge of £55 will apply within the UK with extra charges applicable for delivery outside of the UK. Contact Customer Services for further details.





**Hydraulic Press Accessories** 

\*For models 53436410 & 53436510

# **%** GO1500B

#### **Battery & Transmission Lifting Table 1500kg**

- Universal lifting table with a load capacity of 1500kg (1.5T).
- · Powered by compressed air.
- Sliding cover, allowing convenient battery installation or removal.
   High ground clearance makes it compatible with all workshop cranes on
- Extendible and tiltable top table, by means of a mechanical screw.
- Easy to operate and tilt with self explanatory operations.
  The table features holes with M10 thread, which can be used to mount all types of supports or accessories, including special hooks, brackets, and protective mats for battery packs.
- Button operated table lowering
- Rack safety system, when not being operated, the table locks by means of a mechanical anti-lowering safety wedge.

Photo of the GO1500T for demonstration purposes



# **‰** GO1501 M10 Spacer Kit (15pcs)

- For use with EV & Transmission Lifting Tables GO1000B / GO1500B / GO1500T.
- Spacers can used to raise the battery or transmission off the tale to allow access to the underneath for removing bolts etc.
- Allow you to avoid battery contact with the
- metal table and so prevents arcing.

   Allow for easy access for straps to lift the battery off the table when full battery replacement is required.



90.00

# **GO1503**

## attery Lifting Accessory Kit



- Slotted holes in the foot allow an easy changing/moving of the platform.
   The support columns are height-adjustable and have a thread for screwing the rubbers/spacers.
- Used for platforms with M8 and M10 threaded holes.

- Support foot length: 200 mmMinimum height: 215 mm
- Maximum height: 315 mm
- Usable key for upper pin: \$W32 mm
- Maximum capacity for each support: 100 Kg
  Threads used for top fixing: M8


111

- Fixing screw: M8
- Fixing screw: M10

:1320.00



- Max capacity 1.5T.
   Adjustable between 650mm and
- 2250mm. Works with standard
- engine crane.
   Includes leveling device for safe lifting



- NEW! Induction Heaters


  Induction heating is a non-contact method that can be used to heat metals. The induction heater creates an alternating magnetic field that generates induced currents within the material. It is these induced currents that generate heat.
- The absence of open flames makes work easier, while ensuring safety and economic savings at the same time
- It allows you to work in close proximity to heat-sensitive parts.

- Heat inducers are ideal for a wide range of applications such as:
- corroded bolts/nuts
- Remove or replacing pins or
- bearings
- Heating for straightening
- Preheating before welding

  - Bending
  - Thermal applications



GO1473





TO PLACE AN ORDER CALL 01202 746031



# TO PLACE AN ORDER CALL 01202 746031



Unit 12, 35 Willis Way, Poole BH15 3SZ www.ashleypower.co.uk